

Rental park services for hose linings

We take care of your rental park! We assemble your hose lines **up to DN 305 mm / 12"** including the required couplings for suction and discharge hoses employed at submersible pumps or diesel pumps. All hose lines are tested according the European Pressure Equipment Directive PED 2014/68/EU periodically, repaired or replaced. Of course hose lines are also cleaned.

We swage hoses up to DN 305 mm / 12"

Our services for you:

- Production and development of hose systems (fixed hoses incl. couplings)
- Development of hoses and systems (rubber, plastics, metal)
- Production of rental park hoses
- PE-pipeline production for rental parks, swaged according to your needs
- Pressure tests according to PED 2014/68/EU
- Individual labelling
- Documentation by individual verification, according to EN 10204
- Diverging tests according to your specifications
- Repairs by our testing- and assembly service
- Shipment
- Storage







Grünin G+L oske

www.gruelo.de

GrülottosE Technology



Water S/D 10

The top solution for your rental fleet

Water hose for suction and discharge purposes in tough applications such as in industry, agriculture and construction. The tube is suited for water, sewage, liquid manure, drilling mud and low abrasive materials. The cover is abrasion and weather resistant...

Technical characteristics

Norm: ISO 1307

Temperature range: -25 °C up to +70 °C

Standard length: 40 m

Colour: Black

Construction

Cover: SBR, with fabric impression

Reinforcement: Synthetic textile, steel wire spiral

Lining: SBR, black, smooth

Inner-Ø mm	Inner-Ø Inch	Wall thickness mm	WP bar	BP bar	Bending radius mm	Weight/Meter kg	Article-no.
51	2	5,50	10	30	306	1,759	10056-051
75	3	7,50	10	30	458	2,908	10056-075
102	4	6,50	10	30	610	4,025	10056-102
127	5	8,50	10	30	762	6,298	10056-127
152	6	8,50	10	30	915	8,205	10056-152
203	8	11,00	10	30	1219	12,544	10056-203
254	10	12,00	10	30	1524	15,304	10056-254
305	12	12,00	10	30	1829	22,034	10056-305

